

Product Number: D3551, D3552 **Application: 2015-2016 Chevy Suburban** 

#### Your safety and the safety of others is very important.

- In order to help you make informed decisions about safety, we have provided installation instructions and other information.
- These instructions alert you to potential hazards that could hurt you or others.
- Please do a job safety analysis (JSA) before each task to identify potential hazards for your situation and remove/protect against them.
- You must use your own good judgment, and take your time.

Read and understand all safety precautions and instructions before installing this product.

THIS PRODUCT IS FOR OFFROAD USE ONLY. ALL LIABILITY FOR INSTALLATION AND USE RESTS WITH THE OWNER.

CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE.

SENSORS FIELD OF VIEW WILL BE ALTERED WITH USE OF THE REPLACEMENT BUMPER.

### Injury hazard

#### **Failu**

are to observe these instructions could lead to severe injury or death.	
	Always remove jewelry and wear eye protection.
	Always use extreme caution when jacking up a vehicle for work. Set emergence
	brake and use tire blocks. Locate and use the vehicle manufacturers designated
	lifting points. Use jack stands.
	Always use appropriate and adequate care in lifting components into place.
	Always insure components will remain secure during installation and operation
	Always wear safety glasses when installing this kit. A drilling operation will
	cause flying metal chips. Flying chips can cause serious eye injury.
	Always use extreme caution when drilling on a vehicle. Thoroughly inspect the
	area to be drilled (on both sides of material) prior to drilling, and relocate any
	objects that may be damaged.
	Always use extreme caution when cutting and trimming during fitting.
	Always tighten all nuts and bolts securely per installation instructions.
	Always route electrical cables carefully. Avoid moving parts, components that
	become hot and rough or sharp edges.
	Always insulate and protect all exposed wiring and electrical terminals.
	Always perform regular inspections and maintenance on mounts and related
	hardware.



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

### I. Overview

Congratulations on your purchase of the industries' best and most stylish Chevy Suburban Bumper! This bumper has been **engineered** for strength while keeping the weight down.

Your bumper was designed in 3-D, fabricated, and powder coated... all in the U.S.A.

Enjoy the fit and finish of a quality Chevy Suburban Vengeance Bumper from Fab Fours Inc.



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

#### **II. Parts List**

- D355X replacement bumper
- 50089-HW fastener kit
- Instruction manual

### III. Tools Required

- Socket wrench with extension (ratcheting wrenches may also be convenient)
- 7mm, 8mm, 9mm, 10mm, 15mm sockets and box end wrenches
- 7/16" wrench and 7/16" ratchet wrench
- T15 torx
- Hex key sets
- Flat head screw drivers
- Floor jack and wood block



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

### IV. Vehicle Preparation

1. Open hood and remove the 12 plastic push clips securing the plastic radiator shroud. Using a small screwdriver or pick, carefully pull the centers of the clips up. Once centers are up, the clips are safe to remove. Once the clips are out, shroud will be able to be removed. See Figure 1.



Figure 1

**2.** Using a 10mm socket and ratchet remove the six 10mm bolts securing the upper grille assembly to the radiator support. See Figure 2



Application: 2015-2016 Chevy Suburban




Figure 2

**3.** Next remove the six 7mm bolts securing the inner fender to the bumper cover. See Figure 3. You can turn the wheels while doing this to allow more room to work.





Figure 3



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

- **4.** Next under the front bumper remove the eight 10mm bolts securing the bottom of the bumper to the chassis. Two in the center and three on each side. Finally remove the clips securing the wiring harness to the bumper.
- **5.** Next gently pull back on the grille assembly allowing access to the rear of grille. Then remove the two 10mm bolts securing the grille to the chassis. Next disconnect the fog light wiring harness, finally using a flathead screwdriver depress the lower tabs securing bumper to chassis. See Figure 5.




Figure 5

**6.** Next starting at rear of bumper, gently pull the bumper cover away from vehicle. This may require a good amount of force. Repeat on other side.



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban



- **7.** Bumper is now safe to remove. Using two people pull bumper cover and grille off vehicle in one piece.
- **8.** Lay bumper face down on a soft surface being careful not to scratch grille as it will be reused. Unclip the wiring harness from grille and bumper, you can also remove park assist sensors at this time. Remove the five 10mm bolts from each side of grille securing it to the bumper cover. (Set grille, wiring harness and sensors aside as they will be reused later.)
- **9.** Next remove the crash bar by removing the six (three on each side of crash bar) 15mm bolts shown in Figure 7. Save 15mm bolts as they will be reused in the installation of Fab Fours bumper. If applicable you may also remove tow hooks at this time.



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban




Figure 7




Figure 8

**10.** Next remove the black bumper cover mounts located on each fender (see Figure 8). Remove the three 10mm bolts shown in Figure 9.






Figure 9



Figure 10



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

**11.** Next remove the bumper mount located under each headlight shown in Figure 10. Do so by removing the three torx screws shown in Figure 11.




Figure 11

**12.** Lastly, remove bumper support brackets from back of body mounts (ref image below). Using a 15mm socket remove two bolts from each side.




Figure 12a (passenger side body mount)





Figure 12b (support brackets)



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

### V. Sensor Installation

1. Feed sensor harness through the cutouts in brackets. Make sure that the plug for the OEM harness is on the passenger side of bumper. Zip-tie holes for harness indicated by arrows.




Figure 13

**2.** Sensor housings should all point toward center of bumper, and will clip directly to mounts that are welded in the bumper. See below.





Figure 14 Figure 15



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

3. Sensor harness plug should be fed back through hole so it can be accessed via the grille after bumper is mounted. Refer to **bumper installation step 2.** 

### VI. Bumper Installation

1. Using Fab Fours provided grille mounting braces and ¼" hardware, place them onto the top of the plastic core support shell housing. Install bracing into plastic support by lining up the back edge of the brace with the edge of cutout on both sides. See Figure 16a. Refit the grille to the vehicle by locating the lower plastic clips on the shell of the grille and sliding the clips under the bracket such that engages the slots. See Figure 16b. **Do not bolt in the top of the grille** until the sensor harness plug has been fished back through the hole and plugged in **after bumper installation step 2**. See Figure 16c.




Figure 16a






Figure 16b






Figure 16c



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

2. With the help of at least two others or a lifting device, lift and align the bumper mounts with the frame mounts. At this time it is easiest to run the wiring harness back up into the hole and behind the grill (ref. figure 17a). With the bumper fully supported install the bumper using the 6 OEM bolts, removed in figure 7, and a 15mm socket. **DO NOT FULLY TIGHTEN**.



Figure 17a




Figure 17b



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

- 3. Adjust left and right as needed.
- 4. Tighten all fasteners fully.
- 5. **OPTIONAL:** Trim the inner fender liners to match the higher clearance of your Fab Fours bumper. This can be done with a body saw, rotary tool, or sharp utility knife (New blade strongly recommended). **USE CAUTION WHEN PERFORMING ANY CUTTING OPERATION TO PREVENT VEHICLE DAMAGE OR PERSONAL INJURY**.



Product Number: D3551, D3552 Application: 2015-2016 Chevy Suburban

#### VII. Maintenance/Care

☐ Periodically check and tighten all fasteners.


☐ Stripped, fractured, or bent bolts or nuts need to be replaced.

☐ Keep all surfaces free of dirt, road grime, and standing water to ensure finish longevity.

#### VIII. Contact Information

Fab Fours Inc. Phone (866)-385-1905 2213 Industrial Park Rd. Fax (866)-574-1424

Lancaster, SC 29720 Email Support@fabfours.com



More than expected... Better than expected