


## 1984-1987 Buick Regal Grand National GNX/T-Type - 3.8L V6 Turbo



**Warning:** When working on, under, or around any vehicle exercise caution. Please allow the vehicle's exhaust system to cool before removal, as exhaust system temperatures may cause severe burns. If working without a lift, always consult vehicle manual for correct lifting specifications. Always wear safety glasses and ensure a safe work area. Serious injury or death could occur if safety measures are not followed.

**Step 1:** (Carefully read all instructions before installation) Unbolt the four bolt flange on the Inlet Y-Pipe Assembly at the catalytic converter of the OEM system. To aid in the removal of the OEM exhaust system you may need to cut the tailpipe from the muffler. Once this is done, remove the tailpipe and remaining components from the OEM rubber insulators while being careful not to damage them, since they will be reused to mount the new system.

**Step 2:** Working from front to rear secure the Y-Pipe Assembly to the catalytic converter using the OEM fasteners. To install the Muffler Assemblies you must first mount the supplied universal hangers into the frame rails per Fig.1 (It may be necessary to drill the frame rail holes out and trim the threaded end of the hangers to install them). Use the supplied nuts, one on either side of the frame rail to adjust height. After installing the universal hangers use the supplied 2.50\"/>

**\*\* Magnaflow Performance Exhaust recommends professional installation on all their products**

## 1984-1987 Buick Regal Grand National GNX/T-Type - 3.8L V6 Turbo



Fig. 1

**Step 3:** With all components mounted loosely, adjust the system for overall aesthetics and clearance of frame & bodywork. (MAGNAFLOW recommends at least 1/2" of clearance between the exhaust system and any body panels to prevent heat-related body damage or fire.)

**Step 4:** Once a final position has been chosen for the new system, evenly tighten all fasteners from front to rear. The supplied band clamps must be VERY tight to properly align the pipes and prevent leaks (Approximately 40ft-lbs). U-bolt clamps should be tightened to approximately 30-35ft-lbs. Inspect all fasteners after 25-50 miles of operation and retighten if necessary.